



NANTIAN

YONGKANG NANTIAN INDUSTRY & TRADE CO., LTD.

NANTIAN
GARDEN TOOLS & ACCESSORIES

www.zjnantian.com

📍 Add: No.546, HuaJin Road, HuaJie Town, YongKang, ZheJiang, China
☎ TEL: 0579-87515821 FAX: 0579-87515825 📞 0086-159 2592 2170
✉ sales@zjnantian.com
🌐 www.zjnantian.com

12 YEARS EXPERIENCE
ONE-STOP OEM/ODM





YONGKANG NANTIAN INDUSTRY & TRADE CO., LTD.



Yongkang Nantian Industry and Trade Co., Ltd. is a strong garden tool manufacturer that was found in 2010, which professionally combines development, production and sale as a whole. The main product is Chain Saw, Brush Cutter, Hedge Trimmer, Earth Auger, Water Pump and so on. The products have obtained CE,GS,EMC, Euro V, and other international certifications. Corporate headquarters is located in the Hardware Capital of China - Yongkang, Zhejiang. The factory occupies an area of 18,000 square meters, with beautiful environment and convenient transportation.

The company has advanced production equipment, professional and innovative technicians and experienced workers. With the idea of "technology-based, market-oriented, innovative, fully dedicated to environmental protection". Also, manufacturer management is organized by ISO900:20151 and assessed by intertek. The company is deeply convinced by the customers and has become one of the rapidly developing enterprises in China.

The company is based on "NANTIAN" brand. We can guarantee both product's quality and quantity according to customers' requirements. We offer middle & high quality levels products with exportation to Latin America, Eastern Europe, Western Europe, Central Asia, Middle East, Southeast Asia, and other areas of the world. Over many years, the factory works closely with the customers, because of good stable quality and reputation and service.

What's more, the company attaches importance to quality management and brand building, and strives for well-behaved confidence. All dealers are welcome to discuss cooperation and build excellent enterprises together!

12 YEARS EXPERIENCE
ONE-STOP OEM/ODM



CONTENT

 GASOLINE CHAINSAW BRUSH CUTTER	01
GASOLINE CHAINSAW	03
BRUSH CUTTER	11
MULTI-PURPOSE TOOLS	23
HEDGE TRIMMER	25
GASOLINE WATER PUMP	27
EARTH AUGER	29
GASOLINE MINI TILLER	31
GASOLINE HAND-PUSH BRUSH CUTTER	31
ACCESSORIES	32





This new design machine can be used for different working situation, with low-vibration function, long time working life, efficient stable performance.

NT5800F

GASOLINE CHAINSAW

This new design machine can be used for different working situation, with low-vibration function, long time working life, efficient stable performance.



Parameters	45cc	52cc	58cc
Displacement:	45cc	52cc	58cc
Max power:	1.7kw/7000rpm	2.0kw/7000rpm	2.3kw/7000rpm
Idling speed:	3000±200rpm	3000±200rpm	3000±200rpm
FUEL VOLUME			
Fuel tank capacity:	550ml	550ml	550ml
Oil tank capacity:	260ml	260ml	260ml

Oil Mixture ratio: 25:1



NT-BC430F/BC520F

BRUSH CUTTER

This new design machine can be used for different working situation, with low-vibration function, long time working life, efficient stable performance.



Parameters	43cc	52cc
Engine type:	1E40F-5	1E44F-5
Displacement:	42.7cc	52cc
Max power:	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm
FUEL VOLUME		
Fuel tank capacity:	1200ml	

Oil Mixture ratio: 25:1



Double layer filtration insulates sawdust effectively.



Primer bulb for easy starting, even in the very extreme climates



Ergonomically designed handles with comfortable grip.

Saw Chain and Bar
Equipped with high performance chain and low kickback bar

Front Hand Guard
Reduce the risk of injury

Safety Trigger
Prevents accidental acceleration



Tool free Fuel and Oil Caps
Caps for fuel and oil tank require no extra tools to open or tighten

Anti-Vibration System
Helps to reduce operator fatigue

GASOLINE CHAINSAW

NANTIAN powerful chainsaw, the good choice of professionals and homeowners. Excellent power-to-weight ratio, low-vibration function, efficient stable performance, can find the suitable machines in the different situations.

12 YEARS EXPERIENCE
ONE STOP SERVICE

GASOLINE CHAINSAW

2STROKE

PRIMER BULB



NT2500 GASOLINE CHAINSAW

The most lightweight chain saw, small size, low vibration
Especially for firewood cutting, felling trees and pruning
operations.

12 YEARS EXPERIENCE
ONE-STOP SERVICE



NT3800



2STROKE

PRIMER BULB

NT3800E



EASY START

2STROKE

PRIMER BULB

NT2500 GASOLINE CHAINSAW

Parameters



Displacement: 25.4cc
Max power: 0.9kw/7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 230ml
Oil tank capacity: 160ml



Oil Mixture ratio: 25:1

NT3800 GASOLINE CHAINSAW

Parameters



Displacement: 37.2cc
Max power: 1.2kw/7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 310ml
Oil tank capacity: 210ml



Oil Mixture ratio: 25:1

NT3800E GASOLINE CHAINSAW

Parameters



Displacement: 37.2cc
Max power: 1.2kw/7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 310ml
Oil tank capacity: 210ml



Oil Mixture ratio: 25:1



2STROKE

PRIMER BULB

NT4500 GASOLINE CHAINSAW

Powerful long-lasting, high temperature performance
Particularly suitable for medium density wood felling.



GASOLINE CHAINSAW NT4500E

Powerful long-lasting, high temperature performance
Particularly suitable for medium density wood felling.

12 YEARS EXPERIENCE
ONE-STOP SERVICE

EASY START

2STROKE

PRIMER BULB

NT4500 GASOLINE CHAINSAW

Parameters



Displacement: 45cc 52cc 58cc
Max power: 1.7kw/7000rpm 2.0kw/7000rpm 2.3kw/7000rpm
Idling speed: 3000±200rpm 3000±200rpm 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 550ml 550ml 550ml
Oil tank capacity: 260ml 260ml 260ml



Oil Mixture ratio: 25:1

NT4500E GASOLINE CHAINSAW

Parameters



Displacement: 45cc 52cc 58cc
Max power: 1.7kw/7000rpm 2.0kw/7000rpm 2.3kw/7000rpm
Idling speed: 3000±200rpm 3000±200rpm 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 550ml 550ml 550ml
Oil tank capacity: 260ml 260ml 260ml



Oil Mixture ratio: 25:1

GASOLINE CHAINSAW



NT5200 GASOLINE CHAINSAW

Powerful long-lasting, high temperature performance
Particularly suitable for medium density wood felling.



GASOLINE CHAINSAW NT5200E

Powerful long-lasting, high temperature performance
Particularly suitable for medium density wood felling.



NT5200 GASOLINE CHAINSAW

Parameters	45CC	52CC	58CC
Displacement:	45cc	52cc	58cc
Max power:	1.7kw/7000rpm	2.0kw/7000rpm	2.3kw/7000rpm
Idling speed:	3000±200rpm	3000±200rpm	3000±200rpm
FUEL VOLUME			
Fuel tank capacity:	550ml	550ml	550ml
Oil tank capacity:	260ml	260ml	260ml

Oil Mixture ratio: 25:1

NT5200E GASOLINE CHAINSAW

Parameters	45CC	52CC	58CC
Displacement:	45cc	52cc	58cc
Max power:	1.7kw/7000rpm	2.0kw/7000rpm	2.3kw/7000rpm
Idling speed:	3000±200rpm	3000±200rpm	3000±200rpm
FUEL VOLUME			
Fuel tank capacity:	550ml	550ml	550ml
Oil tank capacity:	260ml	260ml	260ml

Oil Mixture ratio: 25:1



NT6150 GASOLINE CHAINSAW

Powerful long-lasting, high temperature performance,
excellent power-to-weight ratio,
Particularly suitable for heavy duty task.



GASOLINE CHAINSAW NT6200

Robust engine with strong power,
high temperature performance
Particularly suitable for heavy duty task.



NT6150 GASOLINE CHAINSAW

Parameters	62CC
Displacement:	61.5cc
Max power:	2.5kw/7000rpm
Idling speed:	3000±200rpm
FUEL VOLUME	
Fuel tank capacity:	550ml
Oil tank capacity:	260ml

Oil Mixture ratio: 25:1

NT6200 GASOLINE CHAINSAW

Parameters	62CC
Displacement:	62cc
Max power:	3.2kw/7000rpm
Idling speed:	3000±200rpm
FUEL VOLUME	
Fuel tank capacity:	670ml
Oil tank capacity:	350ml

Oil Mixture ratio: 25:1



GASOLINE CHAINSAW

Powerful long-lasting, high temperature performance
Particularly suitable for medium density wood felling



NT5801



NT5802



NT5803



NT5804



GASOLINE CHAINSAW



NT5805



NT5806



NT5807



NT5808



NT5809



	NT5801	NT5802	NT5803	NT5804	NT5805	NT5806	NT5807	NT5808	NT5809
Parameters									
Displacement:	45cc			52cc			58cc		
Max power:	1.7kw/7000rpm			2.0kw/7000rpm			2.3kw/7000rpm		
Idling speed:	3000±200rpm			3000±200rpm			3000±200rpm		
FUEL VOLUME									
Fuel tank capacity:	550ml			550ml			550ml		
Oil tank capacity:	260ml			260ml			260ml		
 Oil Mixture ratio:	25:1								

NANTIAN BRUSH CUTTER

High-performance, powerful engine with high efficiency and fuel economy performance.
Meet the needs of professional users with long time and large area of operations.



Primer bulb for easy starting.



Durable gear box for high intensity working situation



Easy starter ensures easier pulling and quicker starting. Resistance of pulling the start rope can be reduced up to 30%.

Heavy-duty gear case
With a shape specially designed to prevent catching on grass. Grease can be also supplied very easily.

Advanced Antivibration System

Somatomological design handle

Air filter cover
Are easy to remove for fast and easy filter cleaning or replacement



BRUSH CUTTER

The brush cutter can be used for different working situation, with low-vibration function, long time working life, efficient stable performance.

BRUSH CUTTER



High-performance, comfortable and light engine with high efficiency and fuel economy performance.
Very suitable for user like housewife make the grass pruning in the garden, help you easy and funny to complete the work.



Detachable shaft
Detachable shaft allows for easy transport and storage



2STROKE

POWER
BULB



NT-BC260C BRUSH CUTTER

Parameters

Engine type: 1E34F
Displacement: 25.4cc
Max power: 0.7kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME
Fuel tank capacity: 650ml

Oil Mixture ratio: 25:1

BRUSH CUTTER



High-performance, powerful engine with high efficiency and fuel economy performance.
Meet the needs of professional users with long time and large area of operations.



Detachable shaft
Detachable shaft allows for easy transport and storage



EASY START

2STROKE

POWER
BULB



NT-BC330A BRUSH CUTTER

Parameters

Engine type: 1E36F
Displacement: 32.6cc
Max power: 0.9kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME
Fuel tank capacity: 1000ml

Oil Mixture ratio: 25:1



EASY START

2STROKE

POWER
BULB



NT-BC330B BRUSH CUTTER

Parameters

Engine type: 1E36F
Displacement: 32.6cc
Max power: 0.9kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME
Fuel tank capacity: 1000ml

Oil Mixture ratio: 25:1

BRUSH CUTTER

High-performance, powerful engine with high efficiency and fuel economy performance.
Meet the needs of professional users with long time and large area of operations.



Detachable shaft
Detachable shaft allows for easy transport and storage



NT-BC430A/BC520A

BRUSH CUTTER

Parameters

Engine type:	1E40F-5	1E44F-5
Displacement:	42.7cc	52cc
Max power:	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm

FUEL VOLUME

Fuel tank capacity:	1200ml	1200ml
---------------------	--------	--------



Oil Mixture ratio: **25:1**

NT-BC430B/BC520B

BRUSH CUTTER

Parameters

Engine type:	1E40F-5	1E44F-5
Displacement:	42.7cc	52cc
Max power:	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm

FUEL VOLUME

Fuel tank capacity:	1200ml	1200ml
---------------------	--------	--------



Oil Mixture ratio: **25:1**

BRUSH CUTTER

High-performance, powerful engine with high efficiency and fuel economy performance.
Meet the needs of professional users with long time and large area of operations.



Detachable shaft
Detachable shaft allows for easy transport and storage



NT-BC430C/BC520C

BRUSH CUTTER

Parameters

Engine type:	1E40F-5	1E44F-5
Displacement:	42.7cc	52cc
Max power:	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm

FUEL VOLUME

Fuel tank capacity:	1200ml	1200ml
---------------------	--------	--------



Oil Mixture ratio: **25:1**

NT-BC430D/BC520D

BRUSH CUTTER

Parameters

Engine type:	1E40F-5	1E44F-5
Displacement:	42.7cc	52cc
Max power:	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm

FUEL VOLUME

Fuel tank capacity:	1200ml	1200ml
---------------------	--------	--------



Oil Mixture ratio: **25:1**

BRUSH CUTTER

High-performance, powerful engine with high efficiency and fuel economy performance.
Meet the needs of professional users with long time and large area of operations.



Detachable shaft
Detachable shaft allows for easy transport and storage



NT-BC430H/BC520H BRUSH CUTTER

Parameters

Engine type:	1E40F-5	1E44F-5
Displacement:	42.7cc	52cc
Max power:	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml



Oil Mixture ratio: 25:1

NT-BC430W/BC520W BRUSH CUTTER

Parameters

Engine type:	1E40F-5	1E44F-5
Displacement:	42.7cc	52cc
Max power:	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml



Oil Mixture ratio: 25:1

BRUSH CUTTER

High-performance, powerful engine with high efficiency and fuel economy performance.
Meet the needs of professional users with long time and large area of operations.



Detachable shaft
Detachable shaft allows for easy transport and storage



NT-BC41I(R08) BRUSH CUTTER

Parameters

Engine type:	1E40F-6
Displacement:	40.2cc
Max power:	1.4kw/6500-7000rpm
Idling speed:	3000±200rpm

FUEL VOLUME

Fuel tank capacity: 950ml



Oil Mixture ratio: 25:1

NT-BC41I(MKT) BRUSH CUTTER

Parameters

Engine type:	1E40F-6
Displacement:	40.2cc
Max power:	1.4kw/6500-7000rpm
Idling speed:	3000±200rpm

FUEL VOLUME

Fuel tank capacity: 950ml



Oil Mixture ratio: 25:1

BRUSH CUTTER



High-performance, powerful engine with high efficiency and fuel economy performance.
Meet the needs of professional users with long time and large area of operations.



Detachable shaft
Detachable shaft allows for easy transport and storage



NT-BC615

BRUSH CUTTER

Parameters



Engine type: IE48F
Displacement: 62cc
Max power: 2.0kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml



Oil Mixture ratio: 25:1

NT-B45

BRUSH CUTTER

Parameters



Displacement: 41.5cc
Max power: 1.5kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1000ml



Oil Mixture ratio: 25:1

BRUSH CUTTER



4 stroke engine uses overhead Cam mechanism, Smooth operation, Little vibration, Low fuel consumption, Low noise, through the optimization of oil system, lubrication system, heavy parts material to improve gasoline engine combustion efficiency and to prolong service life.



Detachable shaft
Detachable shaft allows for easy transport and storage



NT-BC139

BRUSH CUTTER

Parameters



Engine type: 139F
Displacement: 31cc
Max power: 0.7kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 700ml



4 stroke oil 92# fuel

NT-BC140

BRUSH CUTTER

Parameters



Engine type: 140F
Displacement: 35cc
Max power: 0.9kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 650ml



4 stroke oil 92# fuel



BRUSH CUTTER

High-performance, powerful engine with high efficiency and fuel economy performance. Meet the needs of professional users with long time and large area of operations.



BRUSH CUTTER

The backpack brush cutter fixed engine on the support of ergonomic harness, not only to keep the operator balance, but to reduce the strain on the shoulders. With soft shaft part and loop handle, it can make quick work on the area what is hard to reach for side-attached brush cutter.



LOW BACK-PACK



HIGH BACK-PACK



	NT-BG330	NT-BG430	NT-BG520	NT-BG139	NT-BG140
Parameters					
Engine type:	1E36F	1E40F-5	1E44F-5	139F	140F
Displacement:	32.6cc	42.7cc	52cc	31cc	35cc
Max power:	0.9kw/6500rpm	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm	0.7kw/6500-7000rpm	0.9kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm	3000±200rpm	3000±200rpm	3000±200rpm
FUEL VOLUME					
Fuel tank capacity:	1000ml	1200ml	1200ml	700ml	650ml
Oil Mixture ratio:	25:1	25:1	25:1	4 stroke oil 92# fuel	4 stroke oil 92# fuel

MULTI-PURPOSE TOOLS



Detachable shaft
Detachable shaft allows
for easy transport and storage



NT-MT260

NT-MT330

NT-MT430

NT-MT520

NT-MT140



Parameters

Engine type:	1E34F	1E36F	1E40F-S	1E44F-S	140F
Displacement:	25.4cc	32.6cc	42.7cc	52cc	35cc
Max power:	0.7kw/6500-7000rpm	0.9kw/6500rpm	1.47kw/6500-7000rpm	1.65kw/6500-7000rpm	0.9kw/6500-7000rpm
Idling speed:	3000±200rpm	3000±200rpm	3000±200rpm	3000±200rpm	3000±200rpm

FUEL VOLUME

Fuel tank capacity:	650ml	1000ml	1200ml	1200ml	650ml
---------------------	-------	--------	--------	--------	-------



Oil Mixture ratio: **25:1**

25:1

25:1

25:1



4 stroke oil
92# fuel



MULTI-PURPOSE TOOLS

Multi-purpose tools is the perfect machine for all season garden maintenance, featuring several individual tools. It features a heavy-duty quick release aluminium drive shaft coupling, enabling the attachments to be changed in seconds.





NT-HT230A HEDGE TRIMMER

Parameters

Displacement: 22.5cc
Max power: 0.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME
Fuel tank capacity: 500ml
Oil tank capacity:



This hedge trimmer can be used for different working situation, with low-vibration function, long time working life, efficient stable performance.



Oil Mixture ratio: 25:1

HEDGE TRIMMER



NT-HT230B

HEDGE TRIMMER

This hedge trimmer can be used for different working situation, with low-vibration function, long time working life, efficient stable performance.

Parameters

Displacement: 22.5cc
Max power: 0.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME
Fuel tank capacity: 500ml
Oil tank capacity:



Oil Mixture ratio: 25:1

NT-HT230C

HEDGE TRIMMER

This hedge trimmer can be used for different working situation, with low-vibration function, long time working life, efficient stable performance.

Parameters

Displacement: 22.5cc
Max power: 0.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME
Fuel tank capacity: 500ml
Oil tank capacity:



Oil Mixture ratio: 25:1

GASOLINE WATER PUMP



NT-WP10A

GASOLINE WATER PUMP

Parameters



Mating engine: 1E38F
Max power: 0.9kw/6500-7000rpm
Discharging capacity: 32.6cc

Flow: 8m³/h
Suction height: 8m
Lift height: 30m
Connection system: 1 inch



Oil Mixture ratio: 25:1



NT-WP10B

GASOLINE WATER PUMP

Parameters



Mating engine: 1E40F-6
Max power: 1.4kw/6500-7000rpm
Discharging capacity: 40.2cc

Flow: 8m³/h
Suction height: 8m
Lift height: 30m
Connection system: 1 inch



Oil Mixture ratio: 25:1



GASOLINE WATER PUMP



NT-WP10C

GASOLINE WATER PUMP

Parameters



Mating engine: 140F
Max power: 0.9kw/6500-7000rpm
Displacement: 35cc
Idling speed: 3000±200rpm

Flow: 8m³/h
Suction height: 8m
Lift height: 30m
Connection system: 1 inch



4 stroke oil 92# fuel



NT-WP15

GASOLINE WATER PUMP

Parameters



Mating engine: 1E44F-5
Max power: 1.65kw/6500-7000rpm
Discharging capacity: 52cc

Flow: 8m³/h
Suction height: 8m
Lift height: 35m
Connection system: 1.5 inch



Oil Mixture ratio: 25:1



EARTH AUGER

Powerful driving force, High drilling efficiency, low vibration function, suitable for different working situation, different sizes of drill bits for you choose.



EASY START

2 STROKE

POWER BALL



EASY START

2 STROKE

POWER BALL



NT-G0520A

EARTH AUGER

Parameters



Engine type: 1E44F-5
Displacement: 52cc
Max power: 1.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml



Oil Mixture ratio: 25:1

NT-G0520B

EARTH AUGER

Parameters



Engine type: 1E44F-5
Displacement: 52cc
Max power: 1.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml



Oil Mixture ratio: 25:1

EARTH AUGER

Powerful driving force, High drilling efficiency, low vibration function, suitable for different working situation, different sizes of drill bits for you choose.



EASY START

2 STROKE

POWER BALL



EASY START

2 STROKE

POWER BALL



NT-G0520C

EARTH AUGER

Parameters



Engine type: 1E44F-5
Displacement: 52cc
Max power: 1.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml



Oil Mixture ratio: 25:1

NT-G0520D

EARTH AUGER

Parameters



Engine type: 1E44F-5
Displacement: 52cc
Max power: 1.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml



Oil Mixture ratio: 25:1

NT-MT520

GASOLINE MINI TILLER

With thick luxury frame, safe and comfortable operating system, gasoline mini tiller will let you find more funs in your garden.

Parameters



Engine type: IE44F-5
Displacement: 52cc
Max power: 1.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml
Oil tank capacity:



Oil Mixture ratio: 25:1



NT-HBC520

GASOLINE HAND-PUSH BRUSH CUTTER

With thick luxury frame, safe and comfortable operating system, gasoline hand-push brush cutter will reduce the workloads much.

Parameters



Engine type: IE44F-5
Displacement: 52cc
Max power: 1.65kw/6500-7000rpm
Idling speed: 3000±200rpm

FUEL VOLUME

Fuel tank capacity: 1200ml
Oil tank capacity:



Oil Mixture ratio: 25:1



ACCESSORIES



NT-A01



NT-A02



NT-A03



NT-A04



NT-A05



NT-A06



NT-A07



NT-A08



NT-A09



NT-A10



NT-A11



NT-A12



NT-A13



NT-A14



NT-A15



NT-A16



NT-A17



NT-A18



NT-A19



NT-B01



NT-B02



NT-B03



NT-B04



NT-B05



NT-B06



NT-B07



NT-B08



NT-B09



NT-B10



NT-C01



NT-C02



NT-C03



NT-C04



NT-C05



NT-C06



NT-D01



NT-D02



NT-D03



NT-D04



NT-D05



NT-D06



NT-D07



NT-D08



NT-D09



NT-D10



NT-E01



NT-E02



NT-E03



NT-E04



NT-E05



NT-E06



NT-E07